



### Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part categor	Protection accessories
Accessory / separate part type	Protective cover
Accessory / separate part designation	Lexan protective covers for transmitter-receiver pair
Product compatibility	XUSLB...0720 XUSLDM...0720
Accessory / separate part destination	Safety light curtain type 4
Height	750 mm
Quantity per set	Set of 2

### Complementary

Material	Lexan
Sensing distance reduction coefficient	0.91 Sn
Net weight	0.677 kg

### Environment

Resistance to chemical agents	<p>Acids</p> <p>Not resistant against detergents and cleaners containing alkaline products</p> <p>Not resistant against esters</p> <p>Not resistant against aromatic hydrocarbons</p> <p>Not resistant against silicone oils and greases containing alkaline products</p> <p>Not resistant against ketones</p> <p>Limited resistant against alkalis</p> <p>Not resistant against halogenated hydrocarbons</p> <p>Limited resistant against alcohols</p> <p>Limited resistant against greases and oil</p> <p>Limited resistant against silicone oils and greases without alkaline products</p> <p>Aliphatic hydrocarbons</p> <p>Limited resistant against detergents and cleaners</p> <p>Not resistant against amines</p>
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-25...70 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

### Contractual warranty

Warranty	18 months
----------	-----------