



### Main

|                                       |                                                       |
|---------------------------------------|-------------------------------------------------------|
| Range of product                      | Telemecanique Safety light curtains XUSL              |
| Accessory / separate part category    | Protection accessories                                |
| Accessory / separate part type        | Protective cover                                      |
| Accessory / separate part designation | Lexan protective covers for transmitter-receiver pair |
| Product compatibility                 | XUSLB...1400<br>XUSLDM...1400                         |
| Accessory / separate part destination | Safety light curtain type 4                           |
| Height                                | 1430 mm                                               |
| Quantity per set                      | Set of 2                                              |

### Complementary

|                                        |         |
|----------------------------------------|---------|
| Material                               | Lexan   |
| Sensing distance reduction coefficient | 0.91 Sn |
| Net weight                             | 1288 kg |

### Environment

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Resistance to chemical agents         | Limited resistant against silicone oils and greases without alkaline products<br>Not resistant against amines<br>Limited resistant against alcohols<br>Limited resistant against detergents and cleaners<br>Acids<br>Not resistant against esters<br>Limited resistant against alkalis<br>Not resistant against silicone oils and greases containing alkaline products<br>Not resistant against halogenated hydrocarbons<br>Limited resistant against greases and oil<br>Not resistant against detergents and cleaners containing alkaline products<br>Not resistant against aromatic hydrocarbons<br>Not resistant against ketones<br>Aliphatic hydrocarbons |
| Ambient air temperature for operation | 0...55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Ambient air temperature for storage   | -25...70 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|