



Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part category	Protection accessories
Accessory / separate part type	Protective cover
Accessory / separate part designation	Lexan protective covers for transmitter-receiver pair
Product compatibility	XUSLDM...1720 XUSLB...1720
Accessory / separate part destination	Safety light curtain type 4
Height	1750 mm
Quantity per set	Set of 2

Complementary

Material	Lexan
Sensing distance reduction coefficient	0.91 Sn
Net weight	1576 kg

Environment

Resistance to chemical agents	Not resistant against amines Limited resistant against detergents and cleaners Limited resistant against alkalis Not resistant against esters Not resistant against aromatic hydrocarbons Acids Limited resistant against silicone oils and greases without alkaline products Not resistant against silicone oils and greases containing alkaline products Limited resistant against alcohols Not resistant against halogenated hydrocarbons Not resistant against detergents and cleaners containing alkaline products Limited resistant against greases and oil Aliphatic hydrocarbons Not resistant against ketones
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty	18 months
----------	-----------