


XUSZSC105R

Telemecanique Safety light curtains XUSL,
Column without mirror 1000 mm with cable
gland PG11, Hp = 610 mm



Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part categor	Mounting and fixing accessories
Accessory / separate part type	Fixing column
Offer type	Without mirror
Product compatibility	XUSL.E...16 to XUSL.E...61 with 2 beams
Accessory / separate part destination	Safety light curtain type 4 Safety light curtain type 2

Complementary

Ambient air temperature for operation	-30...55 °C -22...131 °F
Ambient air temperature for storage	-30...70 °C -22...158 °F
Kit composition	1 x cable gland(s), Pg 11
Column height	1000 mm
Height protected	610 mm
Net weight	3.7 kg

Packing Units


Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	20 cm
Package 1 Length	109 cm
Package 1 Weight	5.3 kg

Offer Sustainability


Sustainable offer status	Green Premium product
Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Dimensions

With XUSZFB2



With XUSZFB1



Mounting and Clearance

