
XUSZSC172R

Telemecanique Safety light curtains XUSL, Column without mirror 1670 mm with cable gland PG11, Hp = 1360 mm



Main

IVIAIII	
Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part categor	Mounting and fixing accessories
Accessory / separate part type	Fixing column
Offer type	Without mirror
Product compatibility	XUSL.E121 to XUSL.E136
Accessory / separate part destination	Safety light curtain type 4 Safety light curtain type 2

Complementary

Ambient air temperature for operation	-3055 °C -22131 °F	
Ambient air temperature for storage	-3070 °C -22158 °F	
Kit composition	1 x cable gland(s), Pg 11	
Column height	1670 mm	
Height protected	1360 mm	
Net weight	5.5 kg	

Packing Units

I acking Office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	14.0 cm	
Package 1 Width	20.0 cm	;
Package 1 Length	180.0 cm	
Package 1 Weight	7.6 kg	,

Offer Sustainability


Sustainable offer status	Green Premium product	
Toxic heavy metal free	Yes	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com	

Product data sheet Dimensions Drawings


XUSZSC172R

Dimensions

With XUSZFB2



With XUSZFB1



XUSZSC172R

Mounting and Clearance

