



Main

| | |
|------------------------------|--|
| Range of product | Telemecanique Photoelectric sensors XU |
| Series name | Application |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUY |
| Sensor design | Roller sensor |
| Detection system | Diffuse |
| Type of output signal | Discrete |
| Discrete output type | PNP |
| Product specific application | Conveyor system |

Complementary

| | |
|----------------------|-------------------------------|
| Maximum voltage drop | <2 V at 100 mA (closed state) |
| Length | 388 mm |

Environment

| | |
|---------------------------------------|-----------------|
| Product certifications | CE[RETURN]cULus |
| Ambient air temperature for operation | 0...50 °C |
| Ambient air temperature for storage | -20...80 °C |

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

Offer Sustainability

| | |
|--|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |