

XX230A21KA00M12

ultrasonic sensor cylindrical M30 - Sn=2m -
pump in NO PNP sync - M12

Main

| | |
|-------------------------------|---|
| Range of product | Telemecanique Ultrasonic sensors XX |
| Sensor type | Ultrasonic sensor |
| Series name | Application |
| Sensor name | XX2 |
| Sensor design | Cylindrical M30 |
| Detection system | Diffuse |
| [Sn] nominal sensing distance | 2 m adjustable with teach push-button |
| Material | Plastic |
| Type of output signal | Discrete |
| Discrete output function | 1 NC + 1 NO |
| Wiring technique | 5-wire |
| Discrete output type | PNP |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Electrical connection | Male connector M12 5 pins |
| Product specific application | For 2 filling levels monitoring |
| [Sd] sensing range | 0.12...2 m |
| Beam angle | 10 ° |
| IP degree of protection | IP67 conforming to IEC 60529 |

Complementary

| | |
|---|--|
| Enclosure material | ULTEM |
| Front material | Silicone |
| Thread type | M30 x 1.5 |
| Supply voltage limits | 10...28 V DC |
| Function available | With synchronisation mode |
| [Sa] assured operating distance | 0.12...2 m (teach mode) |
| Maximum differential travel | 2.5 mm |
| Blind zone | 0...120 mm |
| Transmission frequency | 200 kHz |
| Repeat accuracy | 0.9 % |
| Deviation angle from 90° of object to be detected | -10...10 ° |
| Minimum size of detected object | Cylinder diameter 1.6 mm at 0.635 m |
| Status LED | Output state: 1 LED (green/red (flashing)) Setting-up assistance: 1 LED (green/red (flashing)) Distance indication: 1 LED (yellow) |
| Current consumption | 100 mA |
| Maximum switching current | 100 mA with overload and short-circuit protection |
| Maximum voltage drop | 1 V |
| Maximum delay first up | 1000 ms |
| Maximum delay response | 150 ms |
| Maximum delay recovery | 1000 ms |
| Marking | CE |
| Threaded length | 45 mm |
| Height | 35 mm |
| Width | 35 mm |

| | |
|------------|----------|
| Depth | 85 mm |
| Net weight | 0.091 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-5-2 |
| Product certifications | cCSAus[RETURN]UL |
| Ambient air temperature for operation | 0...50 °C |
| Ambient air temperature for storage | -10...80 °C |
| Vibration resistance | +/-1 mm conforming to IEC 60068-2-6 (f = 10...55 Hz) |
| Shock resistance | 30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27 |
| Resistance to electrostatic discharge | 8 kV level 4 conforming to IEC 61000-4-2 |
| Resistance to electromagnetic fields | 10 V/m level 3 conforming to IEC 61000-4-3 |
| Resistance to fast transients | 1 kV level 3 conforming to IEC 61000-4-4 |

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

Offer Sustainability

| | |
|--|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |