

XX7K1A2PAM12CR

Ultrasonic sensors XX, ultrasonic sensor type K
24 VDC + options



Main

Range of product	Telemecanique Ultrasonic sensors XX
Sensor type	Ultrasonic sensor
Sensor name	XX7
Material	PBT (polybutylene terephthalate)
Sensor design	Flat form
Product specific application	For 2 levels monitoring
Type of output signal	Dual-level - pump-out latch
Wiring technique	4-wire
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Discrete output function	1 NO
Discrete output type	PNP
Electrical connection	1 male connector M12 4 pins
[Sd] sensing range	203...254 mm
Beam angle	10 °
IP degree of protection	IP67 conforming to IEC 60529

Complementary

Enclosure material	ULTEM
Front material	Silicone
Supply voltage limits	10...28 V DC
[Sn] nominal sensing distance	254 mm
Sensing window	203
Type of sensing window	Fixed
[Sa] assured operating distance	3.18...228.6 mm (no teach mode)
Blind zone	51 mm
Transmission frequency	500 kHz
Repeat accuracy	0.7 %
Minimum size of detected object	Cylinder diameter 1.6 mm - up to 76.2 mm sensing distance
Status LED	Output state: 2 LEDs (amber) Power: 2 LEDs (green)
Current consumption	60 mA
Maximum switching current	100 mA with overload and short-circuit protection
Maximum voltage drop	<1.5 V
Switching frequency	80 Hz
Maximum delay first up	350 ms
Maximum delay response	5 ms
Maximum delay recovery	1000 ms
Marking	CE
Height	18 mm
Width	18 mm
Depth	18 mm
Length	84.32 mm
CAD overall height	16.25 mm
CAD overall width	84.4 mm
CAD overall depth	16.25 mm
Net weight	0.045 kg

Environment

Standards	IEC 60947-5-2
Product certifications	UL
NEMA degree of protection	NEMA 4X (indoor use only)
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...100 °C
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 (f = 10...55 Hz)
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27
Resistance to electrostatic discharge	8 kV level 4 conforming to IEC 61000-4-2
Resistance to electromagnetic fields	10 V/m level 3 conforming to IEC 61000-4-3
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.652 cm
Package 1 Width	9.652 cm
Package 1 Length	9.652 cm
Package 1 Weight	20.412 g

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------