

XY2CD111H29

Simple rope pull switch, Telemecanique
Emergency stop rope pull switches XY2C, 1NC
+ 1 NO, snap action, 240 VAC, 10 A, XY2CD



Main

Range of product	Telemecanique Emergency stop rope pull switches XY2C
Product or component type	Simple rope pull switch
Device short name	XY2CD
Housing colour	Blue
Overtoltage category	Class I conforming to EN/IEC 61140 Class I conforming to NF C 20-030

Complementary

Trigger cable maximum length	6 m
Body material	Zamak
Head material	Plastic
[Us] rated supply voltage	240 V
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action
Resistance to wrenching	237 DaN operating head 36 daN operating ring
Cable entry number	3 3 entries tapped for Pg 13.5 cable gland for Pg 13.5
Mechanical durability	1500000 cycles
[Ie] rated operational current	3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	400 V (pollution degree 3) conforming to EN/IEC 60947-1 300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14
Compatibility code	XY2CD

Environment

Product certifications	CCC[RETURN]CE
Ambient air temperature for operation	-20...70 °C
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.2 cm
Package 1 Width	14.6 cm
Package 1 Length	6.5 cm
Package 1 Weight	280.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com