## XY2CE4A020H7

# Cable pull switch 300 VAC 10 A XY2CE



### Main

Control button type	Standard momentary stop
Device application	Conveyor systems Presses Test laboratories Woodworking equipment Transfer machines Textiles Packaging Paint lines
Device short name	XY2
Enclosure type	Dust and damp proof weatherproof enclosure for indoor/outdoor

#### Complementary

[In] rated current	10 A	
Cable entry	3 entries tapped for 1/2" NPT cable gland	
Contact code designation	A300 Q300	
Contact operation	Snap action	
Contacts type and composition	2 NO/2 NC	
Depth	104.14 mm	
Device mounting	Surface	
Height	142.2 mm	
Installation direction	Left	
Permissible voltage	300 V	

#### **Environment**

NEMA degree of protection	NEMA 1/4/12	
Product certifications	CSA LR44087 class 3211 03[RETURN]UL listed file E164353 CCN NKCR[RETURN]CE	_

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	15.0 cm	
Package 1 Width	30.0 cm	
Package 1 Length	40.0 cm	
Package 1 Weight	1.4 kg	

#### Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com