

Main

Control button type	emergency stop latching
Device application	Textiles Presses Transfer machines Conveyor systems Woodworking equipment Test laboratories Packaging Paint lines
Device short name	XY2
Enclosure type	Dust and damp proof weatherproof enclosure for indoor/outdoor

Complementary

[In] rated current	10 A
Cable entry	3 entries tapped for 1/2" NPT cable gland
Contact code designation	A300 Q300
Contact operation	Slow make slow break
Control type	RESET push-button
Depth	39.88 mm
Device mounting	Surface
Device mounting	Surface
Height	68.58 mm
Permissible voltage	300 V
Pilot light	With pilot lamp 230 V

Environment

NEMA degree of protection	NEMA 1/4/12
Product certifications	UL listed file E164353 CCN NKCR[RETURN]CSA LR44087 class 3211 03[RETURN]CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.