

XZCE13M785M

Adaptor, metal, tapped hole Pg 13.5, for male connector, 7/8" 16UN, 5 wire



Main

Accessory / separate part designation	5-wire connector adaptor
Accessory / separate part categor	Cabling accessories
Accessory / separate part type	Connector adaptor
Cable composition	5 x 1 mm ²
Thread type	Pg 13.5
[In] rated current	6 A

Complementary

Cable length	100 mm
Total number of wires	5
Electrical connection	1 male connector 5 straight
Cable connector fixing	Screw-on
Body material	Metal
Insulation resistance	> 1000000000 Ohm
Maximum resistance across terminals	5000 mOhm
[Ue] rated operational voltage	250 V AC 300 V DC
Net weight	0.05 kg

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-25...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	15.000 cm
Package 1 Length	4.500 cm
Package 1 Weight	47.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	50
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.905 kg


Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com


Contractual warranty

Warranty	18 months
----------	-----------

Dimensions



Connections and Schemes



BN : Brown
BK : Black
BU : Blue
Y/G : Yellow / Green
WH : White