



Main

Range of product	Telemecanique Cabling components
Accessory / separate part categor	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Electrical connection	Straight female connector M12, 12 pins
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	3 m
Cable outer diameter	6.5 mm
Cable composition	12 x 0.25 mm ²
Wire insulation material	PVC
[Ue] rated operational voltage	30 V DC
[In] rated current	1.5 A
Contact resistance	10 mOhm
Minimum insulating resistance	100 MOhm
Net weight	0.22 kg

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-30...80 °C static
Ambient air temperature for storage	-30...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	16.000 cm
Package 1 Length	16.000 cm
Package 1 Weight	220.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	8
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.090 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------