



Main

Range of product	Telemecanique Cabling components
Accessory / separate part categor	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Electrical connection	Straight female connector 7/8", 4 pins
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	2 m
Cable outer diameter	10.8 mm
Cable composition	4 x 1.5 mm ²
Wire insulation material	PVC
[Ue] rated operational voltage	600 V AC 600 V DC
[In] rated current	10 A
Contact resistance	5000 µOhm
Minimum insulating resistance	1 GΩ
Net weight	0.34 kg

Environment

IP degree of protection	IP67
Product certifications	cULus
Ambient air temperature for operation	-25...80 °C static
Ambient air temperature for storage	-25...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	22 cm
Package 1 Length	24 cm
Package 1 Weight	330 g

Offer Sustainability


California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty

18 months

Dimensions



L : Length of cable

Connections and Schemes

Connectors



RD : Red
WH : White
BK : Black
GN : Green