

XZCR1111064D03

Telemecanique Safety light curtains XUSL,
Series connection jumper, 2 straight M12,
Female/Female con., 0.3 m, 5 pins



Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part type	Jumper cable
Accessory / separate part category	Connection accessory
Accessory / separate part destination	Safety light curtain master/slave XCSR RFID safety switch

Complementary

Product compatibility	XUSL2 XCSRC.2M12 XUSL4
Connector type	M12 female 5 pins straight
Wire insulation material	PUR
Collar material	Nickel plated brass
Cable outer diameter	5 mm
Cable composition	5 x 0.34 mm ²
Cable length	0.3 m

Environment

IP degree of protection	IP67 IP65 IP69K
-------------------------	-----------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.500 cm
Package 1 Width	8.000 cm
Package 1 Length	17.000 cm
Package 1 Weight	40.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.911 kg

Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For all Reach Rohs enquiries contact us at

sustainability@tesensors.com