# XZCR1111064D10

Telemecanique Safety light curtains XUSL, Series connection jumper, 2 straight M12, Female/Female con., 10 m, 5 pins



#### Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part type	Jumper cable
Accessory / separate part categor	Connection accessory
Accessory / separate part destination	Safety light curtain master/slave XCSR RFID safety switch

### Complementary

D 1 1 (199)	VIIO. 6	
Product compatibility	XUSL2	
	XCSRC.2M12	
	XUSL4	
Connector type	M12 female 5 pins straight	
Wire insulation material	PUR	
Collar material	Nickel plated brass	
Cable outer diameter	5 mm	
Cable composition	5 x 0.34 mm²	
Cable length	10 m	

#### **Environment**

IP degree of protection	IP69K IP65
	IP67

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	20.000 cm
Package 1 Length	20.000 cm
Package 1 Weight	364.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.010 kg

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

