



XZCR25K25DL2

IO Link Master Jumper Power cable, Male straight M12 5 pin, Female straight M12 5 pin, PUR, 1.5 mm², 2 m

COMMERCIALISED

Main

Accessory / separate part category	Cabling accessory
Product or component type	Jumper
Jumper cable end 1	5 pins (included earth pin) straight connector with screw-on
Electrical connection	M12, 5 pins (included earth pin)
Jumper cable end 2	M12 female 5 pins (included earth pin) straight connector with screw-on
Cable composition	5 x 1.5 mm ²
IP degree of protection	IP65 IP67

Complementary

Product certifications	CE cULus
[Ue] rated operational voltage	50 V AC < 60 V DC
Wire insulation material	PUR
Electrical connection	1 male + 1 female connectors M12
Insulating resistance	1 GIGAOHM

Packing Units

Package 1 height	25 CENTIMETER
Package 1 width	38 CENTIMETER
Package 1 length	4 CENTIMETER
Package 1 weight	285 KILOGRAM
Package 2 height	15 CENTIMETER
Package 2 width	30 CENTIMETER
Package 2 length	40 CENTIMETER

Package 2 weight 3.15 KILOGRAM

Indivisible sale quantity 1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Updated: 21/10/2025

