XZCRA150941J5

Jumper cable XZ, male straight M12 4 pin, female straight M8 4 pin, PVC 5 m



Main

Accessory / separate part categor	Cabling accessory
Accessory / separate part type	Jumper cable

Complementary

- Complementary		
Jumper cable end 1	M12 male 4 pins straight connector with screw-on and clip-on	
Jumper cable end 2	M8 female 4 pins straight connector with screw-on and clip-on	
Collar material	Metal	
Cable composition	4 x 0.34 mm²	
Cable length	5 m	
Cable outer diameter	5.3 mm	
[Ue] rated operational voltage	60 V AC 75 V DC	
[In] rated current	4 A	
Insulation resistance	>= 1000 MOhm	
Maximum resistance across terminals	5000 mOhm	
Net weight	0.21 kg	
		,

Environment

		#
IP degree of protection	IP68	90
Ambient air temperature for operation	-2585 °C static	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.000 cm	
Package 1 Width	18.000 cm	
Package 1 Length	18.000 cm	
Package 1 Weight	158.000 g	
Unit Type of Package 2	S02	
Number of Units in Package 2	20	
Package 2 Height	15.000 cm	
Package 2 Width	30.000 cm	
Package 2 Length	40.000 cm	
Package 2 Weight	3.488 kg	

Offer Sustainability


Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com
Contractual warranty	
Warranty	18 months



Product data sheet Dimensions Drawings

XZCRA150941J5

Dimensions



L: Length of cable

Product data sheet Connections and Schema

XZCRA150941J5

Connections and Schemes

