XZCRA151140A5

Jumper cable XZ, male straight M12 3 pin, female straight M12 3 pin, PVC 5 m



Main

Accessory / separate part categor	Cabling accessory
Accessory / separate part type	Jumper cable

Complementary

Complementary		
Jumper cable end 1	M12 male 3 pins straight connector with screw-on and clip-on	
Jumper cable end 2	M12 female 3 pins straight connector with screw-on and clip-on	
Collar material	Metal	
Cable composition	3 x 0.34 mm²	
Cable length	5 m	
Cable outer diameter	5 mm	
[Ue] rated operational voltage	250 V AC 300 V DC	
[In] rated current	4 A	
Insulation resistance	>= 1000 MOhm	
Maximum resistance across terminals	5000 mOhm	
Net weight	0.2 kg	

Environment

IP degree of protection	IP69K	3000
Ambient air temperature for operation	-2585 °C static	7

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	17.5 cm
Package 1 Length	17.5 cm
Package 1 Weight	131 g

Offer Sustainability

Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty


Warranty 18 months



Product data sheet Dimensions Drawings

XZCRA151140A5

Dimensions



L: Length of cable

Product data sheet Connections and Schema

XZCRA151140A5

Connections and Schemes

