XZCRA151164D2

Jumper cable XZ, male straight M12 5 pin, female straight M12 5 pin, PVC 2 m



Main

Accessory / separate part categor	Cabling accessory
Accessory / separate part type	Jumper cable

Complementary

- Complementary		
Jumper cable end 1	M12 male 5 pins straight connector with screw-on and clip-on	
Jumper cable end 2	M12 female 5 pins straight connector with screw-on and clip-on	
Collar material	Metal	
Cable composition	5 x 0.34 mm ²	
Cable length	2 m	
Cable outer diameter	5.7 mm	
[Ue] rated operational voltage	250 V AC 300 V DC	
[In] rated current	4 A	
Insulation resistance	>= 1000 MOhm	
Maximum resistance across terminals	5000 mOhm	
Net weight	0.12 kg	

Environment

IP degree of protection	IP69K
Ambient air temperature for operation	-2585 °C static

Packing Units

1 2.000 cm 12.800 cm
12.800 cm
12.000 cm
21.000 cm
90.000 g
S02
40
15.000 cm
30.000 cm
40.000 cm
3.965 kg

Offer Sustainability


Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com
Contractual warranty	
Warranty	18 months



Product data sheet Dimensions Drawings

XZCRA151164D2

Dimensions



L: Length of cable

Product data sheet Connections and Schema

XZCRA151164D2

Connections and Schemes

