

XZCRB4545P14L2

Jumper cable XZ, elbowed female M12 12 pin,
elbowed female M12, 12 pin, 2 m



Main

Accessory / separate part categor	Cabling accessories
Accessory / separate part type	Jumper cable
Female jumper cable end 1	M12 female 12 pins elbowed connector with screw-on
Female jumper cable end 2	M12 female 12 pins elbowed connector with screw-on

Complementary

Collar material	Metal
Cable composition	12 x 0.14 mm ²
Cable length	2 m
Wire insulation material	PUR
Cable outer diameter	8.5 mm
[Ue] rated operational voltage	30 V DC
[In] rated current	1.5 A
Insulation resistance	>= 100 MOhm
Maximum resistance across terminals	5 mOhm
Net weight	0.12 kg

Environment

IP degree of protection	IP65 IP69K IP68
Ambient air temperature for operation	-40...80 °C static
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	20.000 cm
Package 1 Length	20.000 cm
Package 1 Weight	228.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.680 kg

Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For all Reach Rohs enquiries contact us at

sustainability@tesensors.com