

# ZCEGA

Limit switch head, Limit switches XC Standard, ZCE, M16 booted silicone end plunger



## Main

|                            |                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product           | Telemecanique Limit switches XC Standard                                                                                                                                                                                                                                                                                                                               |
| Series name                | Standard format                                                                                                                                                                                                                                                                                                                                                        |
| Product or component type  | Limit switch head                                                                                                                                                                                                                                                                                                                                                      |
| Device short name          | ZCE                                                                                                                                                                                                                                                                                                                                                                    |
| Head type                  | M16 plunger head                                                                                                                                                                                                                                                                                                                                                       |
| Product compatibility      | XCKD<br>XCKP<br>XCKT<br>XCMD                                                                                                                                                                                                                                                                                                                                           |
| Associated body            | ZCMD21L2<br>ZCMD69C12<br>ZCMD21L5<br>ZCMD81L2<br>ZCMD81L1<br>ZCMD21C12<br>ZCMD61C12<br>ZCMD29L2<br>ZCMD21L08R12<br>ZCMD21M12<br>ZCMD29L5<br>ZCMD39L5<br>ZCMD21L1<br>ZCMD25L2<br>ZCMD21L08U78<br>ZCMD29L1<br>ZCMD61M12<br>ZCMD41L2<br>ZCMD39L1<br>ZCMD39L2<br>ZCMD41L5<br>ZCMD41L1<br>ZCMD37L5<br>ZCMD29C12<br>ZCMD25L1<br>ZCMD81L5<br>ZCMD25L5<br>ZCMD37L1<br>ZCMD37L2 |
| Movement of operating head | Linear                                                                                                                                                                                                                                                                                                                                                                 |
| Type of operator           | End plunger spring return metal (with silicone boot)                                                                                                                                                                                                                                                                                                                   |
| Type of approach           | Vertical approach, 1 direction                                                                                                                                                                                                                                                                                                                                         |

## Complementary

|                  |      |
|------------------|------|
| Positive opening | With |
|------------------|------|

## Environment

|                                       |                      |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C          |
| Ambient air temperature for storage   | -40...70 °C          |
| Environmental characteristic          | Standard environment |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 1.5 cm   |
| Package 1 Width              | 4 cm     |
| Package 1 Length             | 1.5 cm   |
| Package 1 Weight             | 18 g     |
| Unit Type of Package 2       | BAG      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 3 cm     |
| Package 2 Width              | 13 cm    |
| Package 2 Length             | 19 cm    |
| Package 2 Weight             | 180 g    |
| Unit Type of Package 3       | S01      |
| Number of Units in Package 3 | 50       |
| Package 3 Height             | 15 cm    |
| Package 3 Width              | 15 cm    |
| Package 3 Length             | 40 cm    |
| Package 3 Weight             | 1.125 kg |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| Circularity Profile                        | No need of specific recycling operations                                                                                                                                                                                                                                                                                                                                          |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|