

ZCKD029TG

Limit switch head, Limit switches XC Standard,
ZCKD, steel roller plunger with boot



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKS XCKL XCKM

Associated body	ZCKM8H29 ZCKS7H29 ZCKMD39 ZCKS6 ZCKS9 ZCKM5H7 ZCKMD39H7 ZCKS1H29 ZCKMD39H29 ZCKL8H7 ZCKLD31 ZCKSD31 ZCKM5 ZCKL6 ZCKS8H29 ZCKMD31 ZCKM7H29 ZCKM8 ZCKS1 ZCKM7 ZCKM6H7 ZCKL5 ZCKSD35 ZCKM7H7 ZCKL1 ZCKS5H29 ZCKSD37 ZCKS5 ZCKS6H29 ZCKL5H7 ZCKSD37H29 ZCKMD37H7 ZCKL6H7 ZCKSD39H29 ZCKM1H7 ZCKM6H29 ZCKMD35H29 ZCKLD39 ZCKMD37H29 ZCKSD39 ZCKM6 ZCKMD31H29 ZCKM8H7 ZCKM1H29 ZCKL7 ZCKMD35H7 ZCKS7 ZCKLD39H7 ZCKMD37 ZCKLD35H7 ZCKLD31H7 ZCKM5H29 ZCKMD35 ZCKM9H29 ZCKSD31H29 ZCKMD31H7 ZCKL1H7 ZCKLD35 ZCKM1 ZCKLD37 ZCKL7H7 ZCKS2 ZCKL8 ZCKS8 ZCKS9H29 ZCKSD35H29 ZCKLD37H7 ZCKS2H29 ZCKM9
Movement of operating head	Linear
Type of operator	Roller plunger spring return metal (with protective boot)
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Temperature variation

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.4 cm
Package 1 Width	6.1 cm
Package 1 Length	3.2 cm
Package 1 Weight	40.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------