Product data sheet Characteristics

ZCKE086

Limit switch head, Limit switches XC Standard, ZCKE, spring rod, -40 °C



Mair

Main	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Multi-directional head
Product compatibility	XCKJ
Associated body	ZCKJD35H29 ZCKJ1H29 ZCKJ8H7 ZCKJ21 ZCKJ6 ZCKJ9 ZCKJD39 ZCKJD39 ZCKJ9H7 ZCKJ2H7 ZCKJ2H7 ZCKJ6H7 ZCKJ5H7 ZCKJ5H7 ZCKJ5BH29 ZCKJ5H7 ZCKJBH29 ZCKJD37H29 ZCKJD37H29 ZCKJD37H7 ZCKJD37H7 ZCKJBH29 ZCKJD37H7 ZCKJD37H7 ZCKJD37H7 ZCKJD37H7 ZCKJD31H7 ZCKJD31H7 ZCKJD31H7 ZCKJD31H7 ZCKJD31H7 ZCKJTH29 ZCKJ11 ZCKJTH29 ZCKJD31H7 ZCKJT ZCKJD35H7 ZCKJD35H7 ZCKJD35H7 ZCKJD35H7 ZCKJD355 ZCKJD35 ZCKJD39H7 ZCKJ2 ZCKJD39H7 ZCKJ2 ZCKJD39H7 ZCKJ2 ZCKJD39H7
Movement of operating head	Multi-directional
Type of operator	Spring rod spring return
Type of approach	Multi-directional approach

Complementary

Switch actuation	By any moving part	
Positive opening	Without	
Net weight	0.125 kg	
Head material	Metal	

Environment

Ambient air temperature for operation	-4070 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Low temperature

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.900 cm
Package 1 Width	3.900 cm
Package 1 Length	16.700 cm
Package 1 Weight	134.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.595 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months