

ZCKE635

Limit switch head, Limit switches XC Standard, ZCKE, side metal plunger, +120 °C



Main

| | |
|----------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch head |
| Device short name | ZCKE |
| Head type | Plunger head |
| Product compatibility | XCKJ |
| Associated body | ZCKJ21 ZCKJ8H7 ZCKJ11H7 ZCKJ11H29 ZCKJ5H7 ZCKJD37H29 ZCKJ6H7 ZCKJ1H7 ZCKJ9 ZCKJ6 ZCKJD39 ZCKJD39H7 ZCKJ7H7 ZCKJ8H29 ZCKJD31 ZCKJ21H29 ZCKJD35 ZCKJD39H29 ZCKJ7 ZCKJ8 ZCKJD35H7 ZCKJ2H7 ZCKJ5H29 ZCKJ9H29 ZCKJ1H29 ZCKJ11 ZCKJ7H29 ZCKJ21H7 ZCKJ2 ZCKJD31H29 ZCKJ5 ZCKJ2H29 ZCKJ9H7 ZCKJD31H7 ZCKJ6H29 ZCKJD37 ZCKJ1 ZCKJD37H7 ZCKJD35H29 |
| Movement of operating head | Linear |
| Type of operator | Side plunger spring return metal |
| Type of approach | Lateral approach, 1 direction |

Complementary

| | |
|------------------|--------|
| Switch actuation | On end |
| Positive opening | With |
| Net weight | 0.2 kg |
| Head material | Metal |

Environment

| | |
|---------------------------------------|------------------|
| Ambient air temperature for operation | 10...120 °C |
| Ambient air temperature for storage | 10...120 °C |
| Environmental characteristic | High temperature |

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

Offer Sustainability

| | |
|--|---|
| Sustainable offer status | Green Premium product |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|