# Product data sheet Characteristics

# ZCKE646

Limit switch head, Limit switches XC Standard, ZCKE, side steel roller plunger horizontal, -40 °C



#### Main

Main	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ1 ZCKJ8H29 ZCKJ1H29 ZCKJ5 ZCKJ5H29 ZCKJ7H29

ZCK E64

range of product	relemedanique Elmit Switches Ao Otandard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ1 ZCKJ8H29 ZCKJ1H29 ZCKJ5 ZCKJ5H29 ZCKJ7H29 ZCKJ7H29 ZCKJD39H29 ZCKJ2H7 ZCKJB7 ZCKJ9H7 ZCKJ9H7 ZCKJ9H7 ZCKJ9H7 ZCKJ9H7 ZCKJ9H7 ZCKJ6H7 ZCKJ6H7 ZCKJB39 ZCKJ11H29 ZCKJ11H29 ZCKJ11H29 ZCKJ11H29 ZCKJ11H29 ZCKJ11H7 ZCKJD37 ZCKJD37 ZCKJD37 ZCKJD37H29 ZCKJ11H7 ZCKJ21 ZCKJ11H7 ZCKJ21 ZCKJ11H7 ZCKJ21 ZCKJ11H7 ZCKJ21 ZCKJ11H7 ZCKJ11 ZCKJ11H7 ZCKJ11 ZCKJ11H7 ZCKJB35 ZCKJ7 ZCKJB38 ZCKJ2 ZCKJ1H7 ZCKJB38 ZCKJ6H29 ZCKJB31H7 ZCKJ6 ZCKJ8H7
Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal (with horizontal roller)
Type of approach	Lateral approach, 2 directions

#### Complementary

Complementary		
Switch actuation	By 30° cam	
Positive opening	With	
Net weight	0.205 kg	
Head material	Metal	

### Environment

Ambient air temperature for operation	-4070 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Low temperature

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

## Offer Sustainability

Green Premium product	
No need of specific recycling operations	
WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
sustainability@tesensors.com	

### Contractual warranty

Warranty	18 months
----------	-----------