

ZCKJ41H29

Limit switch body, Limit switches XC Standard, ZCKJ, plug in, w/o display, 2C/O, snap action, M20



Main

| | |
|-------------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCKJ |
| Body type | Plug-in body |
| Product compatibility | XCKJ |
| Associated head | ZCKE619 ZCKE67 ZCKE61 ZCKE05 ZCKE23 ZCKE21 ZCKE629 ZCKE62 ZCKE66 |
| Body material | Metal |
| Cable entry | 1 entry tapped for M20 x 1.5 cable gland |
| Number of poles | 2 |
| Contacts type and composition | 2 C/O |
| Contact operation | Snap action |
| Number of steps | 2 sequential |
| Contacts material | Silver plated contacts |

Complementary

| | |
|--|---|
| Local display | Without |
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.75...2 x 1.5 mm ² |
| Positive opening | Without |
| Minimum actuation speed | 0.01 m/min |
| [Ie] rated operational current | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 500 V (pollution degree 3) conforming to IEC 60947-1 for contact block 300 V conforming to CSA C22.2 No 14 for contact block 300 V conforming to UL 508 for contact block |
| Maximum resistance across terminals | 0.25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1 |
| Short-circuit protection | 10 A cartridge fuse, type gG |
| Electrical durability | 5000000 Cycles, DC-13 120 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Electrical circuit type | Indicator light module 1 LED DC, 24 V (20...30 V) service life: 100000 h with reverse polarity protection |
| Width | 40 mm |
| Height | 77 mm |
| Depth | 44 mm |

| | |
|-------------------------------|------------------------|
| Net weight | 0.32 kg |
| Terminals description ISO n°1 | (13-14)NO (21-22)NC |

Environment

| | |
|---------------------------------------|--------------------------------------|
| IP degree of protection | IP66 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -25...70 °C for standard environment |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.7 cm |
| Package 1 Width | 4 cm |
| Package 1 Length | 4.4 cm |
| Package 1 Weight | 310 g |

Offer Sustainability

| | |
|--|---|
| Sustainable offer status | Green Premium product |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|