Product data sheet Characteristics

ZCMD4DL1

Limit switch body, Limit switches XC Standard, ZCMD, 2NC+2 NO, silver, snap action, connection, 1 m



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch body
Device short name	ZCMD
Design	Miniature
Body type	Fixed
Associated head	ZCE66 ZCEF0 ZCEF2 ZCE08 ZCE21 ZCE63 ZCE29 ZCE13 ZCE01 ZCE61 ZCE62 ZCE28 ZCE11 ZCE65 ZCE14 ZCE65 ZCE64 ZCE14 ZCE10 ZCE09 ZCE06 ZCE07 ZCE06 ZCE07
Body material	Zamak
Number of poles	4
Contacts type and composition	2 NC + 2 NO
Contact operation	Snap action

Complementary

Complementary		
Product compatibility	XCMD	
Electrical connection	Removable cable	
Cable length	1 m	
Cable composition	9 x 0.34 mm²	
Wire insulation material	PvR	
Contacts insulation form	Zb	
Contacts material	Silver plated contacts	
Positive opening	With	
Minimum actuation speed	0.01 m/min	
[Ui] rated insulation voltage	300 V (pollution degree 3) conforming to UL 508 400 V (pollution degree 3) conforming to IEC 60947-5-1 300 V (pollution degree 3) conforming to CSA C22.2 No 14	
Maximum resistance across terminals	25 mOhm conforming to IEC 60255-7 category 3	
[Uimp] rated impulse withstand voltage	4 KV conforming to IEC 60664 4 kV conforming to IEC 60947-1	
Short-circuit protection	6 A cartridge fuse, type gG	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intermed as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation in the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Electrical durability	5000000 Cycles, DC-13 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 48 V, 2 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 120 V, 1 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Width	30 mm
Height	51 mm
Depth	16 mm
Net weight	0.065 kg

Environment

Ambient air temperature for storage	-4070 °C	
-------------------------------------	----------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	1.6 cm
Package 1 Length	3.0 cm
Package 1 Weight	160.0 g
Unit Type of Package 2	P06
Number of Units in Package 2	480
Package 2 Height	70.0 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	86.28 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	10.16 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

