ZCMV25D44

limit switch body ZCMD - 1NC+1NO - silver - slow action - connection DT04 4P



Main

Series name Standard format Product or component type Device short name ZCMD Design Miniature Body type Fixed Associated head ZCE29 ZCE02 ZCE06 ZCE62 ZCE09 ZCE13 ZCE67 ZCE10 ZCE14 ZCE07 ZCE10 ZCE14 ZCE07 ZCE08 ZCE65 ZCE64 ZCE9 ZCE08 ZCE65 ZCE61 ZCE61 ZCE7 ZCE08 ZCE65 ZCE61 ZCE7 ZCE10 ZCE10 ZCE10 ZCE10 ZCE10 ZCE10 ZCE10 ZCE10 ZCE10 ZCE24 ZCE11 ZCE27 ZCE64 ZCE27 ZCE64 ZCE27 ZCE66 ZCE01 ZCE28 ZCE66 ZCE01 ZCE28 ZCE66 ZCE01 ZCE10 ZCE201 ZCE10 ZCE201 ZCE10 ZCE202 ZCE016 ZCE016 ZCE016 ZCE016 ZCE016 ZCE016 ZCE016 ZCE026 Body material Zamak Number of poles 2 Contacts type and composition Slow-break, break before make	Range of product	Telemecanique Limit switches XC Standard
type Device short name ZCMD Design Miniature Body type Fixed Associated head ZCE29 ZCE06 ZCE62 ZCE08 ZCE09 ZCE13 ZCE67 ZCE10 ZCE14 ZCE07 ZCE08 ZCE65 ZCEG1 ZCE70 ZCE24 ZCE11 ZCE27 ZCE64 ZCE72 ZCE64 ZCE28 ZCE66 ZCE01 ZCE63 ZCE21 ZCE66 ZCE01 ZCE11 ZCE63 ZCE21 ZCE106 ZCE016 ZCE016 ZCE016 ZCE026 Body material Zamak Number of poles 2 Contacts type and composition Slow-break	Series name	Standard format
Design	•	Limit switch body
Body type	Device short name	ZCMD
Associated head ZCE29	Design	Miniature
ZCE02	Body type	Fixed
Number of poles 2 Contacts type and 1 NC + 1 NO composition Contact operation Slow-break	Associated head	ZCE02 ZCE06 ZCE62 ZCE09 ZCE13 ZCE67 ZCE10 ZCE14 ZCE07 ZCE08 ZCE65 ZCEG1 ZCEF0 ZCE52 ZCE24 ZCE11 ZCE27 ZCE64 ZCE72 ZCE66 ZCE28 ZCE66 ZCE01 ZCE63 ZCE01 ZCE63 ZCE21 ZCE106 ZCE216
Contacts type and composition Contact operation Slow-break	Body material	Zamak
composition Contact operation Slow-break	Number of poles	2
		1 NC + 1 NO
	Contact operation	

Complementary

Product compatibility	XCMD
Electrical connection	Male connector DT04-4P, 4 pins
Contacts insulation form	Zb
Contacts material	Silver plated contacts
Positive opening	Without
Minimum actuation speed	0.01 m/min
[le] rated operational current	1 A at 24 V, DC-13 conforming to IEC 60947-5-1 appendix A 3 A at 24 V, AC-14 conforming to IEC 61131-2 Type 1
[Ithe] conventional enclosed thermal current	6 A
[Ui] rated insulation voltage	24 V (pollution degree 3) conforming to UL 508 24 V (pollution degree 3) conforming to CSA C22.2 No 14 24 V (pollution degree 3) conforming to IEC 60947-5-1
Maximum resistance across terminals	25 mOhm conforming to IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	800 V conforming to IEC 60664
Short-circuit protection	6 A cartridge fuse, type gG

Electrical durability	5000000 cycles, DC-13 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Width	30 mm
Height	66 mm
Depth	21 mm
Net weight	0.065 kg

Environment

Ambient air temperature for operation	-4070 °C
Ambient air temperature for storage	-4070 °C

Packing Units

. doming office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	7 cm
Package 1 Length	17 cm
Package 1 Weight	92 g
Unit Type of Package 2	S02
Number of Units in Package 2	50
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.871 kg

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

