

# ZCP08

Limit switch body, Limit switches XC Standard, ZCP, compact, 2 NO, slow break



## Main

|                               |                                                                                                                                                                                                             |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product              | Telemecanique Limit switches XC Standard                                                                                                                                                                    |
| Series name                   | Standard compact                                                                                                                                                                                            |
| Product or component type     | Limit switch body                                                                                                                                                                                           |
| Device short name             | ZCP                                                                                                                                                                                                         |
| Design                        | Compact                                                                                                                                                                                                     |
| Body type                     | Fixed                                                                                                                                                                                                       |
| Associated head               | ZCEH2<br>ZCE28<br>ZCE63<br>ZCE27<br>ZCE13<br>ZCE06<br>ZCE66<br>ZCEH0<br>ZCE07<br>ZCE08<br>ZCE10<br>ZCE67<br>ZCE21<br>ZCE11<br>ZCE14<br>ZCE64<br>ZCE65<br>ZCE05<br>ZCE02<br>ZCE29<br>ZCE01<br>ZCE62<br>ZCE24 |
| Body material                 | Plastic                                                                                                                                                                                                     |
| Number of poles               | 2                                                                                                                                                                                                           |
| Contacts type and composition | 2 NO                                                                                                                                                                                                        |
| Contact operation             | Slow-break, simultaneous                                                                                                                                                                                    |

## Complementary

|                                        |                                                                                                                                                                  |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Associated connection component        | ZCPEF12<br>ZCPEG13<br>ZCPEP20<br>ZCPEN12<br>ZCPEP16<br>ZCPEG11                                                                                                   |
| Electrical connection                  | Open terminal, clamping capacity: 1 x 0.5...2 x 2.5 mm <sup>2</sup>                                                                                              |
| Contacts insulation form               | Zb                                                                                                                                                               |
| Contacts material                      | Silver plated contacts                                                                                                                                           |
| Positive opening                       | Without                                                                                                                                                          |
| Minimum actuation speed                | 6 m/s                                                                                                                                                            |
| Contact code designation               | B300, AC-15 (Ue = 240 V), Ie = 1.5 A conforming to EN/IEC 60947-5-1 appendix A<br>R300, DC-13 (Ue = 250 V), Ie = 0.1 A conforming to EN/IEC 60947-5-1 appendix A |
| [Ui] rated insulation voltage          | 300 V conforming to UL 508<br>500 V (pollution degree 3) conforming to IEC 60947-1<br>300 V conforming to CSA C22.2 No 14                                        |
| [Uimp] rated impulse withstand voltage | 6 KV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1                                                                                                   |
| Short-circuit protection               | 10 A cartridge fuse, type gG                                                                                                                                     |

|                       |                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability | 5000000 Cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width                 | 31 mm                                                                                                                                                                                                                                                                                                                                                               |
| Height                | 65 mm                                                                                                                                                                                                                                                                                                                                                               |
| Depth                 | 30 mm                                                                                                                                                                                                                                                                                                                                                               |
| Net weight            | 0.07 kg                                                                                                                                                                                                                                                                                                                                                             |

## Environment

|                                       |             |
|---------------------------------------|-------------|
| Product compatibility                 | XCKP        |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage   | -40...70 °C |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 7.5 cm |
| Package 1 Width              | 4.1 cm |
| Package 1 Length             | 4.1 cm |
| Package 1 Weight             | 68.0 g |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|