ZCT21N12

Limit switch body, Limit switches XC Standard, ZCT, compact, 1NC+1 NO, snap action, 1/2"NPT



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard compact
Product or component type	Limit switch body
Device short name	ZCT
Design	Compact
Body type	Fixed
Associated head	ZCE27 ZCE65 ZCE28 ZCE63 ZCEH2 ZCE06 ZCE14 ZCE21 ZCE11 ZCE66 ZCE64 ZCE68 ZCE05 ZCE02 ZCE02 ZCE07 ZCE24 ZCE09 ZCE62 ZCE29 ZCE67 ZCE01 ZCE01 ZCE13
Body material	Plastic
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action

Complementary

Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.342 x 1.5 mm ²
Cable entry	2 entries tapped for 1/2" NPT adaptor, cable outer diameter: 48 mm
Contacts insulation form	Zb
Contacts material	Silver plated contacts
Positive opening	With
Minimum actuation speed	0.01 m/s
Contact code designation	B300, AC-15 (Ue = 240 V), le = 1.5 A conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V), le = 0.1 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] rated insulation voltage	300 V conforming to UL 508 500 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to CSA C22.2 No 14
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60664 6 kV conforming to IEC 60947-1
Short-circuit protection	10 A cartridge fuse, type gG

Electrical durability	5000000 Cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.9 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.9 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Width	58 mm
Height	51 mm
Depth	30 mm
Net weight	0.085 kg
Environment	
Product compatibility	XCKT
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Packing Units	
i doking office	
	PCE
	PCE 1
Unit Type of Package 1	
Unit Type of Package 1 Number of Units in Package 1 Package 1 Height	1
Unit Type of Package 1 Number of Units in Package 1	1 3.4 cm
Unit Type of Package 1 Number of Units in Package 1 Package 1 Height Package 1 Width	1 3.4 cm 6.4 cm
Unit Type of Package 1 Number of Units in Package 1 Package 1 Height Package 1 Width Package 1 Length Package 1 Weight	1 3.4 cm 6.4 cm 9.8 cm
Unit Type of Package 1 Number of Units in Package 1 Package 1 Height Package 1 Width Package 1 Length Package 1 Weight	1 3.4 cm 6.4 cm 9.8 cm
Unit Type of Package 1 Number of Units in Package 1 Package 1 Height Package 1 Width Package 1 Length Package 1 Weight Offer Sustainability	1 3.4 cm 6.4 cm 9.8 cm 60 g

Contractual warranty

Warranty	18 months

